

TESTIMONIALS

"Wow, some time went into designing this! Great quality product."

- Matt, Electrician/Fire Alarm Technician

"Highly recommend this product. Simple, quick and easy to install."

- Rob, Electrician

"Awesome!"

- Christian, Fire Alarm Technician



The most versatile Void Detector Bracket



SCAN HERE TO VISIT OUR WEBSITE



AND WATCH A DETAILED INSTALLATION VIDEO

CONTACT

Rapid Bracket Pty Ltd
PO Box 7280
East Brisbane, QLD 4169

✉ Info@rapidbracket.com
🌐 www.rapidbracket.com

www.rapidbracket.com

About

The Patented Rapid Bracket® is the worlds most versatile Void Detector Holder. It allows the easy installation and future maintenance of detectors in inaccessible or hard to reach ceiling spaces from 550mm to 3000mm in height. Using the Rapid Bracket® removes the need for access hatches, leaving a sleek aesthetically pleasing finish.

Constructed from ultra-high heat resistant engineering polymers and ultra-light weight anodized aluminium, the Rapid Bracket® weighs just 1.2kg in its tallest form. Its 128mm opening, means it can be used with a larger variety of detectors. The clever clamping design allows it to be used in ceiling thicknesses ranging from 8mm to 32mm, and gives it the additional ability to be back blocked for some of those lighter duty ceilings or ceiling tiles. Designed for RAPID installation straight from the box.

Features

- ⑦ Constructed from high quality materials
- ⑦ Weighs just 1.2kg in its tallest form
- ⑦ Its 128mm opening, means it can be used with a larger variety of detectors.
- ⑦ The clever clamping design allows it to be used in ceiling thicknesses ranging from 8mm to 32mm
- ⑦ The clamping design gives it the additional ability to be back blocked for some of those lighter duty ceilings or ceiling tiles.
- ⑦ Less screws means less time working above your head
- ⑦ Installs in minutes
- ⑦ Incredibly user friendly
- ⑦ Easy access for future maintenance and testing
- ⑦ Currently successfully used in Australia, UK, Ireland, Spain and more!



FAQs

What detector types are compatible with the Rapid Bracket®?

Most ELV commercial style detectors less than 128mm wide and up to 500 grams in weight.

What size hole do I cut for the Rapid Bracket®?

You can cut the hole 165mm in diameter.

Do i need to reinforce the ceiling?

Because there are an infinite amount of ceiling types and materials, that decision is up to you. The Rapid Bracket® is Ultra strong and light weight, it weighs only 1.25kg in its tallest form.

Can the Rapid Bracket® reach a 3-meter tall ceiling cavity?

Yes, the Rapid Bracket's telescopic tubes give it the ability to be installed in ceiling cavities ranging from just 0.55m, all the way to 3m in height!

What ceiling thicknesses are the Rapid Bracket® compatible with?

The Rapid Bracket® is compatible with ceiling thicknesses from 8mm to 32mm.

How long does it take to install the Rapid Bracket®?

The Rapid Bracket® takes just minutes to be installed!

Where can I find the Rapid Bracket®?

You can purchase the Rapid Bracket® through any of our distribution partners in the UK, Ireland, Spain and Australia.

Do you have other innovative time saving products ?

Yes! Check out the Rapid Base® Ceiling Access Point at www.rapid-base.com

More time saving products coming soon!

www.rapidbracket.com

