

Rapid Bracket Pty Ltd

PO Box 7280

East Brisbane QLD 4169

ABN 67 635 643 597

Contact:

info@rapidbarcket.com

RAPID BRACKET®

VOID DETECTOR HOLDER



Description

The Patented Rapid Bracket® Void Detector Holder allows the installation of fire detectors into inaccessible ceiling spaces from 550mm in depth to 3000mm. Ceiling type thicknesses can range between 8 and 32mm. The Rapid Bracket® is compatible with detectors up to 128mm diameter and is designed for ease of installation and future maintenance of detectors.

The Rapid Bracket® has been specifically designed for ease of installation and future maintenance, as well as being compatible with a greater range of detectors and a larger variety of ceiling types.



Features

- Installs straight out of the box
- Engineered dimensional components
- 165mm Ø cutout for easy access to concealed cables
- Simple click locking Assembly
- Compatible with ceiling thicknesses from 9mm to 32mm
- Can be used in a variety of ceiling types
- Less time working above your head
- High quality components
- · Aesthetically pleasing finish
- Simplifies detection maintenance
- No more man holes

Information

Product code	RBVDH
Cut out size	165mm Ø
Installation type	Recessed with
	165mmø flush face
Installation material	9mm to 32mm
thickness	
Weight	~1.2kg
Material	PBT, Nylon,
	Aluminum,
	Polycarbonate
Cover plate finish	UV resistant bright
	white
Australian made	YES
Patented	YES
Trademarked	YES

